



TOOLING and PLASTICS, INC

950 SE Loop 456
 Jacksonville, TX 75766
 Ofc: 903.586.9894
 Fax: 903.586.8357
www.DLPlastics.com

EQUIPMENT SPEC SHEET - Updated 1.28.21

MACH #	MACHINE TYPE	CORE PULL	SHOT SIZE (OZ.)	SHOT SIZE (LBS.)	APPROX. LBS. per linear inch	CLAMP PRESS (TON)	MAX CLAMP STROKE	MAX DLIGHT	MAX MOLD SIZE (WXH)	MOLD THICKNESS MIN / MAX	BAR SPACE (WXH)	EJECTION STROKE	PLATEN SIZE (WXH)	OPTIONS
1	700 TON VAN DORN	NO	165	10.31	0.49	700	36"/44" *	55"/63" *	53 X 36.5"	14" or 22"/ram	36.5" X 36.5"	6"	53.5 X 53.5	B,D, E
2	95 TON JSW	NO	3.7	0.23	0.05	95	11.81"	25.6"	20.9 X 14.2"	7.1" / 13.8"	14.2" X 14.2"	3.15"	20.9" X 20.9"	B,E
3	150 TON BORCHE	YES	14	0.88	0.10	150	16"	35"	29 x 20"	6.25/ 19.5"	18X18"	5"	26.37X26.37"	B
4	350 TON BORCHE	YES	44.7	2.79	0.20	350	22.83"	48.62"	37 X 28.7"	8.66" / 25.78"	26.3" X 26.3"	7.08"	37.4" X 37.4"	B,D,E
5	300 TON HT VAN DORN	YES	25.4	1.59	0.12	300	24"	49"	37 x 25"	8" / 25"	25x25"	6"	37x37"	B,D,E
6	285 TON BORCHE	YES	28.3	1.77	0.13	285	20.47"	44.09"	32" X 22"	7.67" / 23.62	22.6" X 22.6"	7.08"	32.8" X 32.8"	loaded
8	440 TON BORCHE	YES	66.8	4.18	0.27	440	25.78"	54"	40" X 27"	9.6" / 28.3"	28.7" X 27.5"	8"	41.7" X 40.5"	Loaded
9	715 TON BORCHE	YES	95.1	5.94	0.36	715	34.64	68.89	47" X 32.5"	11.81 - 34.25	36.61 X 35.43"	11.02	52.75 X 51.57	Loaded
10	285 TON BORCHE	YES	28.3	1.77	0.13	285	20.47"	44.09"	32" X 22"	7.67" / 23.62	22.6" X 22.6"	7.08"	32.8" X 32.8"	loaded
11	88 TON BORCHE	YES	5.4	0.34	0.03	88	12.59"	26.77		5.11" / 14.17"	14.17 x 14.17"	3.93"	21.25 x 21.25"	
13	500 TON JSW	NO	74.7	4.67	0.27	500	31.5"	61"	48" X 31.8"	13.78"/ 29.53"	31.8" X 31.8"	7.165"	48" X 48"	B,D,E
14	440 TON BORCHE	YES	51.01	3.19	0.20	440	25.79"	54"	37 X 28.7"	9.6" / 28.3"	28.7" X 27.5"	8"	41.7" X 40.5"	Loaded
15	880 TON-BORCHE	YES	143	8.94	0.45	880	40.35"	78.74"	53.5" X 36.5"	14.96-38.38"	39.7" X 39.7"	11.8"	56.3" X 56.3"	B,D,E
16	700 TON-HS VAN DORN	YES	125	7.81	0.47	700	44"	58"	62" X 36.5"	14.5" /ram	45.5" X 36.5"	6"	62" X 53.5	A,B,D
17	500 TON VAN DORN	YES	80	5.00	0.30	500	40"	53"	53" X 32.5"	11.5 / ram	30.2" X 32.5"	6"	53" X 47"	A,B,D,E
18	1000 TON-HS VAN DORN	YES	260	16.25	0.98	1000	50"	68" **	76" X 44"	22"-37/ ram	52.5" X 44"	8"	76" X 76"	B,D, E
19	1100 TON BORCHE	YES	256	16	0.97	1100	45.3"	88.5"		17.7-43.3"	45.6" X 43.3"	13.77"	68.5 x 66"	Loaded
20	615 TON BORCHE	yes	102.4	6.4	0.36	615	32.2	65.7"		11.81 - 33.4"	34.6" X 33.4"	11.02"	49.2 X 48"	Loaded

OPTIONS CODES: (A) INTRUSION (B) MULTIPLE EJ (D) HYDRO EJECT (E) ROBOTICS INTERFACE

(*) First number is with 8" spacer pillars/ second is with spacers removed

(**) Max daylight is 89.875" and min mold thickness is 40" with ejector box removed and 2 7/8" spacer plate removed and overtravel limit switch bypassed.